

## Welding & Cutting Solutions Oxygen/fuel Gas Cutting





The Weld Safe oxy / fuel gas cutting unit is the ideal solution for demanding on site applications.

Heavy duty all steel construction means the unit can easily withstand the rigours of daily use on factory and construction sites. With all steel construction and a footprint size of 900mm sq it provides a stable platform for equipment reducing the risk of falling cylinders compared to traditional cylinder trolleys. Forklift pockets all around and lifting eye are standard.

The unit houses two oxygen and one fuel gas cylinder providing extended cutting time in-between cylinder changeovers. Regulators are mounted on a manifold assembly and cylinder connections are via flexible hoses. This reduces the risk of damage during cylinder change over. Very often in cutting applications regulators without gauges are fitted due to the risk of damage and frequency of replacement. With our system twin gauge regulators are a more viable option enhancing safety. Two of the major causes of flashbacks are incorrect pressure settings and damaged equipment.

Locking doors front and back means the Weld Safe cutting unit provides the ultimate in security on site. Not only does our unit provide security from theft but also from unauthorised use by un trained personnel.



Manufacturers of Weld Safe products

Clwyd Welding Services Ltd, Unit 6, Hawarden Industrial Park, Manor Lane, Deeside, Flintshire, CH5 3PZ Tel : 01244 531667 Fax : 01244 531842 email : cws-ltd@hotmail.co.uk www.cws-ltd.com